

Name	Notes	CSS Selector(s)	Custom Head
Global background color	Used to change background color from light grey to something else. We typically recommend retaining the default.	<code>body { background: [hex or rgb]; }</code>	
Global typeface	Impacts all text. Default is Lucida Grande. Changing this can create some spacing issues.	<code>body { font-family: [typefaces]; }</code>	
Flexible branding - top	Inactive by default. When activated, inserts an image above the standard header.	<code>#flex-branding-top { background: [hex or rgb]; }</code>	
Flexible branding - bottom	Inactive by default. When activated, inserts an image beneath standard content.	<code>#flex-branding-bottom { background: [hex or rgb]; }</code>	
Standard header	This is active by default and generally contains the event organizer's logo. We typically update the background property to match the logo.	<code>header { background: [hex or rgb]; }</code>	
Global announcement	This is a message which appears at the very top of the page. By default, it is inactive. You can set background color and text color.	<code>#announce-global { background [hex or rgb]; color: [hex or rgb]; }</code>	
Session header	An additional bar which appears as a header for a session, with text indicating which session a user is in.	<code>#header-session { background: [hex or rgb]; }</code>	
Session header text	This is the text inside the session header. This is how you change the text color.	<code>#header-session h1 a { color: [hex or rgb]; }</code>	
Session header text (no ellipsis)	This code will override the default styling, and allow a Session Title to wrap across multiple lines.	<code>#header-session h1 a { text-overflow: clip; white-space: normal; }</code>	
Section headers	There are a number of sections with contain links to various things. At the top of the list is a header bar.	<code>.section-header { background: [hex or rgb]; }</code>	
Section header text	Changing the color of a link list header requires another line of code. You may want to change both the color and text-shadow.	<code>.section-header h1 { color: [hex or rgb]; text-shadow: none; }</code>	
Section header action links	There are occasionally action links that appear to the right of the header text. For example, we might have a "Create" or "new" link.	<code>.section-header a { background: [hex or rgb]; color: [hex or rgb]; text-shadow: none; }</code>	
Section header action link hover state	Yes, these links have a hover state as well	<code>.section-header a:hover { background: [hex or rgb]; }</code>	
Poll list header	Polls are a special kind of link list but can be overridden similarly.	<code>#dashboard-polls .section-header { background: [hex or rgb]; color: [hex or rgb]; text-shadow: none; }</code>	
Poll list action link	This is the "Create Poll" button that moderators can see. You may also need to change the left border color.	<code>#dashboard-polls .section-header a { background: [hex or rgb]; color: [hex or rgb]; border-left-color: [hex or rgb]; text-shadow: none; }</code>	
Poll instructions	Attendees see these instructions when polls are visible.	<code>#dashboard-polls .section-instructions { background: [hex or rgb]; color: [hex or rgb]; }</code>	
Social Q&A list header	Social Q&A are a special kind of link list but can be overridden similarly.	<code>#dashboard-questions .section-header { background: [hex or rgb]; color: [hex or rgb]; text-shadow: none; }</code>	
Social Q&A list action link	This is the "Ask" button that attendees can see. You may also need to change the left border color;	<code>#dashboard-questions .section-header a { background: [hex or rgb]; color: [hex or rgb]; border-left-color: [hex or rgb]; text-shadow: none; }</code>	
Social Q&A instructions	Attendees see these instructions when Social Q&A is visible.	<code>#dashboard-questions .section-instructions { background: [hex or rgb]; color: [hex or rgb]; }</code>	
Social Q&A no upvote	Takes away the ability for participants to upvote	<code>#dashboard-questions .vote { display: none !important; }</code>	
Social Q&A Remove "X"	Takes away the ability for moderators to delete a question	<code>#dashboard-questions .utility.remove { display: none !important; }</code>	
Social Q&A Remove "check mark" button	Takes away the ability for moderators to check a question as complete	<code>#dashboard-questions .utility.complete { display: none !important; }</code>	
Social Q&A Remove the "heart" button	Takes away the ability for moderators to highlight a question for later	<code>#dashboard-questions .utility.save { display: none !important; }</code>	
Social Q&A Remove the "+" when the approval filter is on.	This prevents questions from being able to be pushed out to attendee devices, and keeps the questions only in the moderator view	<code>#dashboard-questions .approve { display: none !important; }</code>	
Moderator Sign In button	This is for the sign-in button itself	<code>.btn-moderator-login { display: none !important; }</code>	
Session Dashboard - Announcement Heading	To hide the announcement, use the CSS rule "display: none;"	<code>#dashboard-announcement h2 { display: none; }</code>	
Session Announcement - Creating hyperlink	Add text that is hyperlinked to another page within the announcement. Replace (INSERT LINK) with the url of the page and (INSERT TEXT) with the text you would like to appear.	<code>(INSERT TEXT HERE)</code>	
Session Dashboard - Bottom	This is a specially named section at the bottom of the session, which in V1 is only used for the moderator sign in button, or the session settings button (if a user is signed in as a moderator)	<code>#session-bottom</code>	

Name	Notes	CSS Selector(s)	Custom Head
Admin sign-out/logout button		.btn-admin-logout	
Social Q&A Instructions (Text)	Change the text (in quotations) on the Social Q&A labels & Instructions. This uses the "Custom Head" section.		<pre><script> var custom_labels = { session_dashboard_qa: "Questions", session_dashboard_ask: "Ask", session_dashboard_no_questions: "There are no questions right now...", ask_question_header: "Add a question", ask_question_field_label: "What's your question?", question_added_transition_normal: "Your question is being added! Please wait just a moment ...", question_added_transition_filter: "Your question is being added. Because the Q&A Filter is enabled, a Moderator must approve it first.", ask_question_filter_message: "After submitting, your question will enter a moderation queue for approval." }; </script></pre>
Session Evaluation Button Label	Change the session evaluation button label to something different than "Evaluate This Session" (put the following code within the "Custom Head" section within the custom branding page.		<pre><script> var custom_labels = {'evaluate_session_button': 'New Text'}; </script></pre>
Social Q&A, Presenter List Heading	Change the text (in quotations) to customize the text that normally says "For whom is this question" when the Social Q&A Panel feature is enabled.. This uses the "Custom Head" section.		<pre><script> var custom_labels = { ask_question_presenter_list_heading: "For whom is this question" }; </script></pre>
Social Q&A, Presenter 'prefix' adjustment	Change the text (in quotations) to customize the text that normally says "for" as the prefix before a presenter's name when the Social Q&A Panel feature is enabled.. This uses the "Custom Head" section.		<pre><script> var custom_labels = { session_dashboard_social_qa_presenter_prefix: "for" }; </script></pre>
Session Evaluation - Choose Another Session button	When this is updated, it is typically to hide it (for various reasons)	.btn-choose-another-session	
Go Back Button	Button at top of page after attendee responds to poll	.btn-inverse	
Redirect Header Image Link to Separate URL	Add to Custom Head Section and Replace "New URL here"		<pre><script> \$(document).ready(function(){ \$("#header h1 a").attr("href", "new URL here"); }); </script></pre>
Unlink Header Image (No redirect to homepage)	Add to Custom Head Section		<pre><script> \$(document).ready(function(){ \$("#header h1 a").attr("href", "#"); }); </script></pre>
Navigation Panel Color	Background color of the navigation panel menu	.sidebar-panel { background: [hex or rgb]; }	
Date/Time Headers Admin/Moderator Setting Headers	Background color for Admin setting labels, Moderator setting labels, and date/time headers on multi-session apps.	#main .link-list h1 { background: [hex or rgb]; }	

Name	Notes	CSS Selector(s)	Custom Head
Bar Chart Colors	Up to 15 can be specified, but not all need to be used.	<pre> .bar-chart .row-1 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-2 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-3 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-4 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-5 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-6 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-7 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-8 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-9 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-10 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-11 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-12 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-13 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-14 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart .row-15 td.poll-percentage-bar span { background: [hex or rgb]; background-image: none; } .bar-chart td.poll-percentage-bar span { background: none; border: none; background-image: none; } </pre>	
Slide background image (light theme)	Add a background image to light themed live content slides	<pre> .slide-light { background-image: url("URL_TO_IMAGE"); } </pre>	
Slide background image (dark theme)	Add a background image to dark themed live content slides	<pre> .slide-dark { background-image: url("URL_TO_IMAGE"); } </pre>	
Hide Beatles gif	Hides the checkin/checkout gif	<pre> .session-checkin-status-modal-waiting .gif { display: none; } </pre>	

Name	Notes	CSS Selector(s)	Custom Head
Move Moderator Button Down	This will add more space between the check-in button and the "Sign Into Moderate" button so attendees don't get confused	<pre>.btn-moderator-login { margin-top: 500px; color: #ccc; }</pre>	
Hide the Check-Out Button	For sessions where check-out isn't required, this code will let you remove the check-out button within a session		<pre><style> .attendance-bar-btn-checkin { display: none !important; visibility: hidden !important; } </style></pre>
Move the QR Code on Poll Slide (Brand Bar v2)	QR codes appear by default in the lower right hand corner of the slide. This code will move the QR code to the top of your page.	<pre>.slide-brand-bar-qr { bottom: auto; top: 3vh; }</pre>	
Move Logo to Bottom of Poll Slide (when using the QR code)	If a logo is set up to appear on your poll slides, and you're moving the QR code to the top, you will want to move your logo to the bottom.	<pre>.slide-brand-bar-logo { position: absolute; bottom: 3vh; display: block; width: 100%; box-sizing: border-box; }</pre>	
Create a Session- Time zone set up instructions	Add language to the "Create a Sessions" page, instructing Admins on what time zone to use.		<pre>"<script> /* SESSION TIME ZONE SCRIPT */ \$(function () { \$.fn.ignore = function(sel){ return this.clone().find(sel ' ">*)').remove().end(); }; var regEx = /in\s(\{([\^}]+)\}) (.+)\$/; \$('<div class="form-subtext"><p>Use this format if event is occurring outside Central Time:
{8:00 AM to 10:00 AM} Location</p></div>"); \$("input[name='start_time']").parents(".form-row").after("<div class='form-subtext'><p>Use the appropriate equivalent in Central Time</p></div>"); \$("input[name='end_time']").parents(".form-row").after("<div class='form-subtext'><p>Use the appropriate equivalent in Central Time</p></div>"); }); </script>"</pre>